§ 109.525

§ 109.525 Cranes: Working loads.

The master or person in charge shall ensure that tables indicating the maximum safe working loads for the various working angles of the boom, where the boom is rated at varying capacities depending on the radius, and the maximum and minimum radius at which the boom may be safely used, are conspicuously posted near the controls and are visible to the operator when working the crane.

§ 109.527 Cranes: Operator designation.

- (a) The master or person in charge shall designate, in writing, each crane operator.
- (b) The master or person in charge shall ensure that only designated operators operate cranes.
- (c) The master or person in charge shall ensure that each designated operator is familiar with the provisions of the API Recommended Practice for Operation and Maintenance of Offshore Cranes, API RP 2D, First Edition (Oct. 1972) with supplement 1.

Subpart G—Miscellaneous

§ 109.555 Propulsion boilers.

The master or person in charge and the engineer in charge shall ensure that—

- (a) Steam pressure does not exceed that allowed by the certificate of inspection; and
- (b) The safety valves, once set, are not tampered with or made inoperative.

[CGD 73–251, 43 FR 56828, Dec. 4, 1978, as amended by CGD 95–028, 62 FR 51208, Sept. 30, 1997]

§ 109.557 Flammable and combustible liquids: Carriage.

The master or person in charge shall ensure that—

- (a) Flammable and combustible liquids in bulk are not carried, except as allowed by endorsement to the Certificate of Inspection:
- (b) Portable tanks are handled and stowed in accordance with subparts 98.30 and 98.33 of this chapter and the provisions of 49 CFR parts 171 through 179 that apply to portable tanks; and

- (c) Grades B and lower liquids are-
- (1) Authorized, by the Commandant, to be carried; and
- (2) Carried only in fixed independent or integral tanks.

[CGD 73–251, 43 FR 56828, Dec. 4, 1978, as amended by CGD 84–043, 55 FR 37413, Sept. 11, 1990]

§ 109.559 Explosives and radioactive materials.

Except as authorized by the master or person in charge, no person may use explosives or radioactive materials and equipment on a unit.

§ 109.563 Posting of documents.

The master or person in charge shall ensure that the following are posted under glass in the pilot house or control center:

- (a) General arrangement plans for each deck showing—
 - (1) Each fire retardant bulkhead;
- (2) Each fire detecting, manual alarm, and fire extinguishing system;
 - (3) Each fire door;
- (4) Each means of ingress to compartments; and
- (5) Each ventilating system, including the location of each damper, fan, and remote means of stopping the fans.
- (6) For units constructed on or after September 30, 1997, and for existing units which have their plans redrawn, the symbols used to identify the aforementioned details shall be in accordance with IMO Assembly resolution A.654(16). The identical symbols can be found in ASTM Adjunct F 1626 (incorporated by reference, see §109.105).
- (b) The stability letter issued by the Coast Guard.
- (c) Each SOLAS and Coast Guard certificate issued to the unit.

[CGD 73-251, 43 FR 56828, Dec. 4, 1978, as amended by CGD 95-028, 62 FR 51208, Sept. 30, 1997; USCG-2000-7790, 65 FR 58462, Sept. 29, 20001

§ 109.564 Maneuvering characteristics.

(a) The master or person in charge of each self-propelled unit of 1,600 gross tons and over shall ensure that a maneuvering information fact sheet is prominently displayed in the pilothouse.